

8-foot Longarm Quilting Frame Table Top Kit

Installation Instructions

Parts Lists

PART #	DESCRIPTION	QTY
QF01501-RAW	4-Foot Table Top Section	2
QF00043	Double-sided Foam 118 inches	1

Tools Needed: Scissors for cutting foam tape
(not included).

- **IMPORTANT:** Removing the frame poles will make it easier to place the table-top sections.
 - **IMPORTANT:** Before installing table-top sections, confirm that guide rails and tracks are in the correct position, by placing the machine and carriage on the tracks and rolling it from end to end, checking for smooth movement and no binding.
1. Cut the double-sided foam tape to fit the cross-bar supports and apply the adhesive side of the foam tape to all six cross-bar supports.

2. Remove the protective cover from the tape on the three cross-bar supports on the right side of the frame.
3. Starting at the right vertical brace, butt the end of one table-top section against the brace and align it between the guide rails. Make sure the table-top section is between the front and rear guide rails and does not overlap the lip of either guide rail. Once the table-top section is correctly positioned, press it onto the foam tape.
4. Remove the protective cover from the foam tape on the three remaining cross-bar supports.
5. Butt one end of the second table-top section end against the end of the installed table-top section and align between the rails. When correctly positioned, press the table-top section onto the foam tape.

