



# MOXIE

**OWN. EVERY. STITCH.**

Now every stitch can be yours — from pieced top to finished quilt. You've got eighteen inches of free-motion freedom at your fingertips and an unrivaled resolve to quilt to the finish line.

Getting started is easy. The Moxie ST Quick Start Guide is right here in the box and educational goodies like in-depth how-to videos, and a detailed, downloadable user manual are available at [HandiQuilter.com/Moxie-ST/](https://HandiQuilter.com/Moxie-ST/). Always up-to-date and available for your reference. Every Moxie ST comes with support from your local Handi Quilter retailer. Handi Quilter longarm quilting experts provide a wealth of quilting knowledge at [HandiQuilter.com/video-library/](https://HandiQuilter.com/video-library/).

Quilt without qualms, adventure with attitude – you've got Moxie.



Connect with us online and show us your Moxie!

[#quiltwithmoxie](https://twitter.com/quiltwithmoxie)

## GET YOUR QUILT ON!

This accessory box has everything you need to get your new Moxie set up and ready to go:

- Moxie ST Quick Start Guide
- How-To Quilt Kit
- Moxie ST Decals
- BILT App Download Instructions
- Power Cord
- Machine Thread Mast
- Machine Spool Pin
- Bobbin Winder Thread Mast
- Bobbin Winder Spool Pin
- Needles - Sizes 110/18 and 110/16
- 2.5mm, 3mm, and 4mm Hex Drivers
- 8mm/10mm Wrench
- EZ-Pen Oiler Bottle
- Lint Brush
- Bobbin Case Screwdriver
- One Set Bobbin + Bobbin Case
- Four Additional Bobbins
- Open-Toe Hopping Foot

FEATURING 3D  
INTERACTIVE  
INSTRUCTIONS

**BILT.**<sup>®</sup>

Download on the  
App Store

GET IT ON  
Google Play

SEE ENCLOSED FOR APP DETAILS!



## BASTING YOUR QUILT

Basting is placing your top with the batting and backing, using a method to attach the three layers together so they don't shift or wrinkle while quilting. There are many ways to accomplish this.

- 1. Prepare your quilt top:** press your quilt top very well. It's recommended to press your seams towards the darker fabric. Trim any frayed threads.
- 2. Batting:** Use a quality batting for your project. Cut a piece that is at least 4" larger than your quilt top on each side.
- 3. Prepare your backing:** Backing should be at least 5" larger than each side of the quilt top. Piece the back if needed, and be sure to press all seams. If you are using a wide back, be sure to press it too!
- 4. Layer the top, batting and backing:**


First, fold each of the layers:

**Top:** fold in half both vertical then horizontal with the wrong side out

**Batting:** fold in half both vertical and horizontal.

**Back:** fold in half both vertical and horizontal.

- Place the back down on a table wrong side up, very smooth.
- You should be able to see the fold line down the center both across and up and down.
- Lay the batting on top, matching the fold lines then opening up the batting.
- This will keep the batting centered on the quilt no matter how big the quilt will be. Smooth it out.
- Add the quilt top, matching to the fold lines on the batting.
- Unfold the quilt top and smooth it out with your hands. Smooth each layer as you place it.
- When all three layers are even and smooth, secure the layers together. You can use 1" safety pins, spray basting, or stitch with a basting stitch.



Check out our  
Basting Video

